

MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

C18209N21

Valve connector Form A, 2P+Earth, Profile Gasket PG9

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A



PRODUCT DESCRIPTION

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

SPECIFICATIONS

Circuit	No circuit
IP Class	IP65
Cross-Section Max	1,5 mm ²
Cable Diameter Max	8 mm
Cable Diameter Min	6 mm
Cable entry CVL	PG9
Color House	Black
Central Material	Polyamide
LED indicator	No
Connector	DINA 43650
Temperature range to	90 °C
Temperature range from	-40 °C
Current max	16 A
Rated voltage	250 V AC/300 V DC

Packing Materials	NBR
Colour LED	No LED
Screw and Gasket	Profile NBR gasket & screw
Manufacturer Part No	1210230238

