



## SURFACE MOUNTED SIREN BU1/ PANEL MOUNTED BUZZER BU2/BU3

B100510004

Panel BUZZERBU1 12VDC

- High noise level 108 dB
- IP66 embedded cable



### PRODUCT DESCRIPTION

#### BU2/BU3

- Quick and easy installation
- Adjustable noise level at front (approx. 10 dB )
- Pulsating sound

### APPLICATION AREA BU1

Surface mounted buzzer with high sound level and high IP-class. With its embedded cable, the siren is easily fitted on the machine without any encapsulation.

### APPLICATION AREA BU2/BU3

Small panel mounted buzzer with flat terminal connection. The sound is easily adjusted through a window at the front and the sound can be trimmed up to approx. 10 dB

### SPECIFICATIONS

Color House	Black
Diameter	60 mm
IP Class	IP66
Mounting	Screw
Nominal current max	0,3 A
Nominal current min	0,3 A
Number of tones	1
Sound level max	108 dB
Sound level min	108 dB
Supply Voltage	12 V

Supply Voltage DC Max	15 V DC
Supply Voltage DC Min	6 V DC
Temperature range from	-20 °C
Temperature range to	70 °C
Tone frequency max	2400 Hz
Tone frequency min	2200 Hz
Weight	110 g

