

## HEATING ELEMENT 10-30W - HGK 047

HGK

04700.0-00

HGK 047 10W Heater with cable, 110-250V ac/dc

- Dynamic heating (PTC element)
- Compact
- Energy saving
- Quick connector for DIN rail



### PRODUCT DESCRIPTION

The heat source in the element consists of a PTC element – a semi-conductor that adapts its output to the ambient temperature.

The PTC element has a high starting current and provides full output almost immediately. The current then falls quickly and the element is thereafter self-regulating, meaning that the warmer the surroundings, the less output produced by the element.

Thanks to the chimney effect, meaning that the colder air is drawn into the element's bottom and discharged at the top, good self-circulation is achieved for the heated air.

The heating element is best installed in smaller cabinets so as avoid condensation or that the temperature falls beneath the minimum level.

### SPECIFICATIONS

Approvals	CE, EAC, Gost R, RoHS, VDE
Cable length	300 mm
Depth	50 mm
Heat Output	10 W
Heater	Anodized aluminum
Height	50 mm
Humidity Storage	<90% RH
IP Class	IP44
Nominal voltage	120-240 V AC/DC

<b>Operating Humidity</b>	< 90% RH
<b>Operational Temperature</b>	-45°C ... +70°C
<b>Pre fuse (slow)</b>	2 A
<b>Protection Class</b>	I (earthed)
<b>Starting Current Max</b>	1 A
<b>Storage temperature</b>	-45°C ... +70°C
<b>Weight</b>	0,1 kg
<b>Width</b>	25 mm
<b>Voltage max</b>	265 V ac/dc
<b>Voltage min</b>	110 V ac/dc

