

ELECTRONIC THERMOSTAT 24V DC - ET 011

ET

01190.0-00 ET 011 Thermostat, 0-60°C, change over, 24V dc

- Fully electronic
- · Small hysteresis
- · Potential free contact





PRODUCT DESCRIPTION

ET 011 is an electronic thermostat that is primarily used to control high DC loads. The floating contact can be used as an NC or NO contact, and can therefore control heating elements, cooling units or alarms for temperatures outside of a specified range. In contrast to many mechanical thermostats, ET 011 has low hysteresis and thus a narrow temperature range. Thanks to this, the setting can be more precise and with lower temperature variations in cabinets.

SPECIFICATIONS

Approvals	CE, EAC, RoHS
Contact resistance	<10 mΩ
Control range temperature from	0 °C
Control range temperature to	60 °C
Depth	46 mm
Detection	PTC
Height	67 mm
Humidity Storage	<90% RH
Hysteresis Temperature	3K
Inrush Max	16 A
IP Class	IP20
Operating Humidity	< 90% RH
Operational Temperature	-40°C +60°C

Storage temperature	-45°C +80°C
Tolerance for switch on	0 °C
Tolerance switch off	0 °C
Weight	0,08 kg
Width	50 mm
Voltage max	28 V dc
Voltage min	20 V dc

