

SOLENOID CONTROLLED SWITCH KSS20

S20FSBFC/O424D

Solenoid controlled switch, 2 NO+2 NC, 24 DC, enclosed

- Solenoid controlled key driven electrical switch interlock
- Panel mount or enclosed
- 2 NC+2 NO or 4 NC contacts



PRODUCT DESCRIPTION

The KSS is a heavy-duty solenoid controlled key driven electrical switch interlock ideal for the controlled isolation or switching of low current. This product is used where a process can send a signal to release a key, e.g. a robot has to finish a cycle prior to isolation. Upon removal of the key, the KSS switch contacts change to isolate the process. This type of isolator should be used for short term, off load isolation. The unit is ready for mounting into an existing panel or for surface mounting within its own IP65 rated lockable steel enclosure. The KSS is manufactured from either brass or stainless steel making it suitable for use in standard or harsh corrosive environments.

SPECIFICATIONS

Approvals	CCC, CE, CSA, UL
Conforming To	EMC, LVD, MD
Contact Current Max	20 A
Contact Current Min	5 mA
Contact Voltage Max	400 V
Contact Voltage Min	20 V
IP Class	IP65
Material Protection	Painted steel
Materials Locks	Brass
Temperature ambient from	-25 °C
Temperature ambient to	55 °C

Weight

2 kg

