

# DATALOGIC - S8 - MINIATURE PHOTOELECTRIC SENSOR

IO-link versions available

S8-PR-5-G00-XG 950801540 Through Beam Emitter M8 Connector

- Compact size (14 x 42 x 25mm)
- M8 Connector or M12 Pig-tail
- Available in IP69K stainless steel
- LED or laser emission
- · Now with IO-link versions



#### PRODUCT DESCRIPTION

The S8 photoelectric series offers the most advanced functions for background suppression, detection of transparent objects and colour mark detection, in addition to the traditional functions for the detection of opaque objects and for small objects thanks to the high resolution obtained through the models with laser emission.

IP69K requirements are met using a sturdy metal housing made of stainless steel and carry IP69K protection and certifications for use with most industrial detergents and can be used on automatic machines for the processing of food and beverage packaging and the pharmaceutical industries.

#### Features & Benefits:

- ·Standard optic functions for objects detection
- ·Detection of clear objects on reflective backgrounds
- ·Models with IP69K 316L stainless steel housing
- ·Compact housing

### Applications:

- ·Food & Pharma
- ·Beverage & Bottling
- ·Packaging lines

## **SPECIFICATIONS**

Approvals	CE, UL
Dimension (mm)	14 x 42 x 25
Distance Max	25000 mm
Distance Min	0 mm
Electrical connection	M8 4 pole connector
Function	Dark On/Light On
IP Class	IP67

LED indicator  Lens material  Light type  Material of body	Yes PC, PMMA Red LED
Light type	
	Red LED
Material of body	
	ABS plastic
Output current max	0,1 A
Photocell technology	Through beam emitter
Power consumption max	0,015 A
Reaction time	0,5 ms
Sensitivity setting	No
Supply voltage	12-30 V DC
Temperature range bearing, from	-20 °C
Temperature range bearing, to	70 °C
	-10 °C
Temperature range from	
Temperature range from  Temperature range to	55 °C
Supply voltage  Temperature range bearing, from  Temperature range bearing, to	12-30 V DC -20 °C 70 °C

