

HONSBERG - TZ1 SERIES FLOW METER

Piston

TZ1-015GR020
Flow meter 1/2", 4-20 l/min

- For liquids up to 100 bar
- Flow from 2 l/min. to 250 l/min. liquid 1-100 cSt
- With or without needle valve



PRODUCT DESCRIPTION

Model TZ1 is a mechanical piston-type flow meter. Thanks to its robust design it is highly suitable in heavy industrial or more demanding applications.

SPECIAL VERSIONS


- 3" to 600 l/min.
- Special scales for oil or gas
- Switch function (NC or NO)

SPECIFICATIONS

Contact Rating Max	5 A
Flow Max l/min Double	20 l/min
Flow Range Max	20 l/min
Flow Range Min	4 l/min
IP Class	IP65
Material Bolt	Brass
Material of body	Bronze
Material of seals	NBR
Materials Spring	Stainless steel 301
Pressure Range Max	100 bar
Temperature range of media to	90 °C
Type of flow component	Flowmeter

Weight

1,6 kg



Type	G"	H mm	L mm	SW mm	Weight kg
YZ1-008GR	1/4	212	68	29	1,6
YZ1-019GR	3/8	212	68	29	1,6
YZ1-019GR	1/2	212	68	29	1,6
YZ1-020GR	3/4	212	73	32	1,7
YZ1-023GR	1	216	87	41	2,0
YZ1-032GR	1 1/4	226	98	52	2,8
YZ1-040GR	1 1/2	228	113	59	3,1
YZ1-050GR	2	236	137	72	6,4
YZ1-065GR400	2 1/2	268	160	85	7,5
YZ1-080GR600	3	268	140	100	8,7

