

HONSBERG - MR1K SERIES FLOW SWITCH

Piston

MR1K-008GM004
"Flow switch 1/4", 0,4-4 l/min"

- Switching Range 0,4..60 l/min H₂O
- Water (oils, gases and aggressive media available on request)
- G $\frac{1}{4}$ up to G1
- Brass or Stainless Steel Wetted Parts
- Max Pressure 200 bar



PRODUCT DESCRIPTION

Model MR1K is a flow switch for liquids and air/gases. It is in a robust and compact version. The switch can be ordered in a large variety of special versions including integrated flow meter, selectable switching range and high pressure version.

SPECIAL VERSIONS

- AIR VERSION
- INTEGRATED FLOW METER WITH VISUAL SCALE
- HIGH PRESSURE VERSION 500 BAR
- DOUBLE SWITCH HEADS

SPECIFICATIONS

Contact Rating Max	50 VA
Flow Max l/min Double	10 l/min
Flow Range Max	4 l/min
Flow Range Min	0,4 l/min
IP Class	IP65
Material Bolt	Brass
Material of body	Nickel-plated brass
Material of seals	NBR
Materials Spring	Stainless steel 301

Pressure Range Max	200 bar
--------------------	---------

Temperature range of media from	-20 °C
---------------------------------	--------

Temperature range of media to	120 °C
-------------------------------	--------

Type of flow component	Flow Switches
------------------------	---------------

Weight	1,3 kg
--------	--------

Viscosity Max	30 cSt
---------------	--------

Viscosity Min	1 cSt
---------------	-------

Voltage AC max	120 V
----------------	-------

