

NON ILLUMINATED PUSHBUTTON

Super Flush Head

L23AA01

PUSH-B FLUSH SP-RTN RED

- IP66 / IP69K
- Spring return
- Low profile flush mount



PRODUCT DESCRIPTION

Super flush pushbutton heads that mount in a 30.5mm hole with protection rating IP66 / IP69K

Ideal for applications where a tamper proof, low profile button is required as only protrudes from front of panel by 2.8mm.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Available in multiple colours in spring return with a metallic chrome bezel.

Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

| | |
|-------------------------------------|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Red |
| Function | Spring return |
| Illuminated | No |
| Impact resistance | IK05 |
| IP Class | IP66 |
| Recommended Torque | 3 Nm |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 70 °C |

| | |
|------------------------|------------------------|
| Temperature range from | -25 °C |
| Temperature range to | 70 °C |
| Type/Model | Super flush pushbutton |

