


SCREW TERMINAL COVERS AND WARNING SIGNS

AD, SAD, FAD, ZAD, TWMF

2958.2

AD 3/1000 mm, Transparent cover profile

- Assembly cover profiles
- Individual terminal covers
- Yellow or White
- Transparent cover profile
- RRK Cross connect covers



PRODUCT DESCRIPTION

Some regulations require that the mains power terminals must be covered.

This then discourages any operation of the screws or cross connector while 'Live'.

The EA, AD, SAD, FAD and ZAP covers are mainly available in yellow (labelled with a lightning flash) are used to cover the cross connect channel and screw holes of the terminal.

EA, AD & SAD covers are for the screw terminal range, where the FAD are for pressure spring and ZAD are for the tension spring range.

The BS 1 marker pen or the EMS labelling system can be used to label the white variants. The AD 4, is designed to cover four terminals of various sizes and is secured by two plastic screws.

The AQ 4 is used on the older RK series of screw terminals and covers the cross connect channel only, to cover the screw in cross connectors.

To complete the range the AD 3 is a transparent cover that can be cut to length and mounted using the TWMF partition plates.

SPECIFICATIONS

Color	Transparent
Country of origin	DE
Flamklass	UL94-V2
Height	68,5 mm
Length	90 mm
Material	Polyamide 6.6
Operating temperature from	-40 °C
Operating temperature to	105 °C
Pack Size	1

Tariff code	39162000
Weight	320 g
Width	1000 mm