

SI1/SI2 ROPE PULL SWITCH

601.4735.001

Rope pull switch SI1-U2Z AK R-RAST, 2x50 m

- Rope length capabilities up to 100 metres
- Die-cast aluminium switch body



PRODUCT DESCRIPTION

Because of their specifications governed by corresponding standards, these cable pull switches are used exclusively as safety command devices. These switches are available in metal enclosures as well as in insulation-enclosed versions. They are operated manually by pulling on the attached cable. Thanks to their pretension, these switches, which feature a switching contact with overlap, execute a switching function when the cable is pulled or in the event of cable breakage.

Features:

- Die-cast aluminium switch body
- Aluminium plated cover
- Zinc die-cast pull ring
- 2 x M20 x 1.5 cable entries
- Conforms to VDE 0660 T100, DIN EN 60947-1, IEC 60947-1
- Conforms to VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1
- Protection class IP 65 according to IEC/EN 60529
- B10d = up to 2 Mio

SPECIFICATIONS

Contact type	2 NO, 2 NC
Lin length max	2x50 m
IP Class	IP65
Temperature range from	-30 °C
Temperature range to	80 °C
Height	99 mm
Width	139 mm
Depth	165 mm
Cable entry	M20x1,5

Voltage Max	240 V
Material	Aluminium
B10d	2x 1000 000

