

IEC INLET FILTER FN9280, 2-POLE SWITCH AND DUAL-FUSE HOLDER

FN9280-1-06

1 A IEC inlet filter, 2-pole switch, dual-fuse holder

- 2- pole "0-1" -switch
- Dual-fuse holder, fuses Ø5x20 mm
- 1-10 A/50-400 Hz
- Faston or spring cage terminals
- Good attenuation performance



PRODUCT DESCRIPTION

Choosing FN 9280/90 product line brings you the rapid availability of a standard filter associated with the necessary safety acceptances and a high attenuation performance. For higher attenuation performance the FN 9290 family with a dual stage filter and identical panel cut-out can be used.

TYPICAL APPLICATIONS

- Portable electrical and electronic equipment
- Consumer goods
- EDP and office equipment
- Single-phase and switch-mode power supplies
- Test and measurement equipment
- Medical electrical devices (MD) and In-Vitro-Diagnostics (IVD) equipment
- Audio/Video, information and communication technologies

SPECIFICATIONS

Capacitance Cx	220 µF
Capacitance Cy	2,2 nF
Flamklass	UL94-V2
Inductance	10,9 mH
Nominal current	1 A
Resistance	1000 kΩ
Temperature range from	-25 °C
Temperature range to	85 °C
Weight	0,105 kg

1A types

