

NON ILLUMINATED SELECTOR SWITCH

Key Handle

L21LA00
KEY-SWITCH 2 POS STABLE 455

- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Multiple key profile options



PRODUCT DESCRIPTION

Non illuminated selector switch head that is key operated and mounts in a 22.5mm hole with protection rating IP66 / IP69K
Combine with separate clip and contact blocks to make complete switch assembly.

Each head supplied with 2 x keys.

Key profile 455 is standard.

Key profile 1424A available at no extra cost.

Other key profiles available at additional cost please enquire for details.

Available in 2 or 3 position, latching or spring return in various switching angles and key free options.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

SPECIFICATIONS

Angle	45°
Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Black
Function	Stable
Illuminated	No
Impact resistance	IK05

IP Class	IP66, IP69, IP69K
Key removable	0
Number of positions	2
Protection Class	II (double insulated)
Recommended Torque	3 Nm
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Key
Weight	31,2 g

