

GELBAU - CONTROL UNIT 352.4/362.0

3003.5246Z2
Evaluator 24VDC



- 2 NO+1 CO output
- Safety category 3 in accordance with EN954-1
- Automatic or manual reset
- One or two inputs





PRODUCT DESCRIPTION




Control unit for the monitoring of sensing strips in dangerous applications. It is also suitable for use on motorised gates which, in line with the standard, must have relays conforming to safety category 3. A low current is transmitted from the control unit connectors (Z1 and Z2) through the sensing strip, and a closed circuit is formed via a resistor (8.2 kΩ). The control unit outputs cuts the power if anyone/anything presses the sensing strip and also following a short-circuit or open circuit.

TECHNICAL DATA

Supply voltage		24 V AC/DC, 230 V AC
Tolerance		-15 % to +10 %
Consumption (operation)		4 W
Relay outputs:	Safe	2 NO (single)
	Signal	1 CO
Max. contact voltage		250 V AC/24 V DC
Max. contact current		6 A AC/2 A DC
Fuse outputs		4 A
Disconnection time		15 ms
Max. length of sensing strip		100 m
Max. cable length to the sensing strip		50 m (min. 0.5 m ²)
Status indication		6xLED
Cable connection		2xPG9 and 2xPG11 (included)
Ingress protection class		IP65
Ambient temperature		-20 °C to +55 °C
Installation		4xM5
Mechanical service life		3x10 ⁷
Safety category		3 in accordance with EN954-1
Standard		EN1760-2, ZH1/494

Conforming to	MD, LVD, EMC
Approvals	 

Technical characteristics

Depending on safety requirements	
• Force guided contacts	
• Internal/external redundancy	
User benefits	
• Safety category 3 in accordance with EN954-1	 Strip activated
• 2 NO and 1 CO output	 Fault in the safety circuit
• Contact load 4A	 Output activated
• LED status indication	
• Monitoring of external contactors	

DIMENSIONS

(mm)

CONNECTION

352.4 (One input)	362.0 (Two inputs)
<hr/> 1. One sensing strip. Manual reset. Monitoring of external contactors.	<hr/> 4. Two sensing strips. Automatic reset.
<hr/> 2. One sensing strip. Automatic reset. Monitoring of external contactors.	<hr/> 5. Several sensing strips. Automatic reset.
<hr/> 3. Two sensing strips. Manual reset. Monitoring of external contactors.	

NOTE!

Input 1 (Z1-Z2) cuts output 13-14. Input 2 (Z3-Z4) cuts output 23-24.

ORDER NUMBER

Order no.	Description
3003.5240Z2	Control unit 352.4, 2 NO+1 CO, one input, cat. 3, 230 V AC
3003.5246Z2	Control unit 352.4, 2 NO+1 CO, one input, cat. 3, 24 V DC

3003.6206Z	Control unit 362.4, 2 NO, two inputs, cat. 3, 24 V DC
3003.6200Z	Control unit 362.0, 2 NO, two inputs, cat. 3, 230 V AC

SPECIFICATIONS

Approvals	CE, TÜV NORD
Cable length to clip list max	50 m (min. 0,5 m ²)
Conforming To	EMC, LVD, MD
Contact Current Max	6 A AC/2 A DC
Contact Voltage Max	250 V AC/24 V DC
Disconnection	15 ms
Fuse output	4 A
IP Class	IP65
PL	e enl. SS-EN ISO 13849-1:2008
Power Consumption	4 W
Supply voltage	24 V DC
Temperature ambient from	-20 °C
Temperature ambient to	55 °C
Terminal Strip Length Max	100 m
Tolerance max	10 %
Tolerance min	-15 %

