ORLACO

IP CAMERAS

ORL0103810
AF-Zoom HD-E IP camera, Alu

- IP69K rated enclosure
- Video stream is accessible via TCP/IP
- Good vibration resistance, G50



PRODUCT DESCRIPTION

Orlaco AF Zoom HD-E and PTZ HD-E IP cameras are a sturdy 30x optical zoom Ethernet cameras with IP connection. These cameras can be used in a computer network on cranes, vehicles and vessels. The video stream is accessible via TCP/IP and therefore easily integrated into a computer network.
Both models are shock and vibration-proof, filled with nitrogen, 100% waterproof, have heated lens glass and provide the best possible image in all conditions. In addition, the cameras have a 0 lux night vision mode and a built-in brightness function for improved view in dark situations.

AF Zoom HD-E

The powerful camera, with an overall 30x zoom is available in an aluminium as well as a stainless steel version. You can control the camera via a computer network. Via a network switch multiple Orlaco cameras can be connected to a computer network. The camera images are accessible via the Orlaco SmartView software or via third party video management software (VMS).

PTZ HD-E

This powerful 360 degree rotating PTZ camera with an overall 30x zoom is available in an aluminium as well as a stainless steel version. The camera has a 180 degree lifting angle and can rotate 180 degrees to the left and 180 degrees to the right (360 degrees) with a speed of 12.5 degrees per second. You can control the camera via a computer network. Via a network switch multiple Orlaco cameras can be connected to a computer network. The camera images are accessible via the Orlaco SmartView software or via third party video management software (VMS).

SPECIFICATIONS

Cable length	5000 mm
IP Class	IP68
Material	Anodized aluminum
Supply Voltage DC Max	30 V DC
Supply Voltage DC Min	18 V DC
Temperature range from	-40 °C
Temperature range to	85 °C
Vibration Resistance	50G