

# **ORLACO - FAMOS**

ORL0171220 CAMERA FAMOS 102 PAL MIRROR



- Robust construction for extreme environments
- 12 or 24 V DC
- operating temperature -40 to +85 °C
- Epoxy-filled, better protection against moisture



## PRODUCT DESCRIPTION

These cameras are available in several different viewing angles to suit the various applications they can be used in. For example, if you want to see details in a long way, choose a narrower opening angle and instead you want a cross-section view, choose a further opening angle. Orlaco cameras are suitable for all types of vehicles, regardless of whether you need a power camera, back camera or side camera.

Orlaco's new FAMOS camera is not gas-filled as the traditional clover camera has been before, but it's epoxy-filled instead. This has provided better protection against moisture.

# **SPECIFICATIONS**


Camera Angle	102
Image Format	PAL
IP Class	IP68, IP69K
Supply Voltage DC Max	24 V DC
Supply Voltage DC Min	12 V DC

Temperature range from	-40 °C
Temperature range to	85 °C
Vibration Resistance	50G



Electrical connections
Front side of molded 4p male connector

1 = Coax core = Video signal
2 = Coax screen = Video GND
3 = Red = 12...24V/DC
4 = Black/orange = 0V
Shielding To connector housing



Electrical connections
Front side of molded 4p male connector

1 = Coax core = Video signal
2 = Coax screen = Video GND
3 = Red = 12...24V/DC
4 = Black/orange = 0V
Shielding To connector housing

