

## **ORLACO - FAMOS**

ORL0171140 Camera FAMOS 60° NTSC

- Robust construction for extreme environments
- 12 or 24 V DC
- operating temperature -40 to +85 °C
- · Epoxy-filled, better protection against moisture



## PRODUCT DESCRIPTION

These cameras are available in several different viewing angles to suit the various applications they can be used in. For example, if you want to see details in a long way, choose a narrower opening angle and instead you want a cross-section view, choose a further opening angle. Orlaco cameras are suitable for all types of vehicles, regardless of whether you need a power camera, back camera or side camera.

Orlaco's new FAMOS camera is not gas-filled as the traditional clover camera has been before, but it's epoxy-filled instead. This has provided better protection against moisture.

## SPECIFICATIONS

Camera Angle	60
Image Format	NTSC
IP Class	IP68, IP69K
Supply Voltage DC Max	24 V DC
Supply Voltage DC Min	12 V DC

## **ORLACO**°

Temperature range from	-40 °C
Temperature range to	85 °C
Vibration Resistance	50G



 Electrical connections

 Front side of molded 4p male connector


 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing



 Electrical connections

 Front side of molded 4p male connector

 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing

0

