

ORLACO - FAMOS

ORL0171230 Camera FAMOS 118 ° NTSC MIRROR

- Robust construction for extreme environments
- 12 or 24 V DC
- operating temperature -40 to +85 °C
- · Epoxy-filled, better protection against moisture



PRODUCT DESCRIPTION

These cameras are available in several different viewing angles to suit the various applications they can be used in. For example, if you want to see details in a long way, choose a narrower opening angle and instead you want a cross-section view, choose a further opening angle. Orlaco cameras are suitable for all types of vehicles, regardless of whether you need a power camera, back camera or side camera.

Orlaco's new FAMOS camera is not gas-filled as the traditional clover camera has been before, but it's epoxy-filled instead. This has provided better protection against moisture.

SPECIFICATIONS

Camera Angle	118
Image Format	NTSC
IP Class	IP68, IP69K
Supply Voltage DC Max	24 V DC
Supply Voltage DC Min	12 V DC

ORLACO°

Temperature range from	-40 °C
Temperature range to	85 °C
Vibration Resistance	50G



 Electrical connections

 Front side of molded 4p male connector


 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing



 Electrical connections

 Front side of molded 4p male connector

 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing

0

