

## DATALOGIC - S62 - COMPACT PHOTOELECTRIC SENSOR

S62-PA-5-G00-XG

FOTOCCELL EMITTER, M12-Contact

- High precision with LED or Laser emission
- Standard 50 x 50 dimensions
- Embedded cable or M12 rotatable connector
- PNP, NPN, PNP/NPN or SPDT Relay output



### PRODUCT DESCRIPTION

S62 photoelectric sensor line offers compact dimensions and competitive prices for all basic and advanced models. All universal optic functions are available in the standard 50 x 50 x 18 mm compact plastic housing with IP67 mechanical protection.

Laser emission models for high resolution detection are also available in polarised retro reflective, diffuse proximity and background suppression.

The sensor allows a great versatility of installations with Vac/dc multivoltage power supply and SPDT relay output, as well as 10-30 Vdc versions with PNP/NPN configurable output.

The S62 series is the first choice when looking for a photoelectric sensor, with the best price and performance ratio in a compact standard case.

#### Features & Benefits:

- High-resolution sensors with LED or LASER emission
- High installation flexibility
- Sensitivity/distance adjustment trimmer
- Embedded cable or M12 rotatable connector
- PNP, NPN, PNP/NPN or SPDT Relay output

#### Applications:

- Automatic machines
- Packaging lines
- Transportation lines
- Automatic warehouses

### SPECIFICATIONS

<b>Approvals</b>	CE, UL
<b>Dimension (mm)</b>	18 x 50 x 50
<b>Distance Max</b>	25000 mm
<b>Distance Min</b>	0 mm
<b>Electrical connection</b>	M12 4 pole connector



