

DATALOGIC - S300-PA - MAXI SENSOR

S300-PA-1-G00EX

- Long detection distances
- AC and DC power supply versions
- Relay / Transistor output
- Terminal Connection
- IP67



PRODUCT DESCRIPTION

The S300-PA series of advanced MAXI photoelectric sensors represents the most suitable solution for standard applications thanks to its excellent cost/performance ratio. The series offers a wide range of models and functions in order to guarantee easy use and installation. The series presents 5 different models with through beam optical function up to 50m, retro reflective up to 15m, polarised retro reflective up to 10m, diffused proximity at 2m and background suppression at 2m. All the models are available both Vdc from 12 to 30V and Vac/Vdc free-voltage from 24 to 240V.

FEATURES & BENEFITS

- Excellent optical performances
- Sturdy plastic housing with IP67 mechanical protection
- Wide range of operating temperatures ranging from -25 to 55°C
- Timing function from 0.6-16 s ON-delay, OFF delay ONE SHOT
- Terminal block for both Vdc and Vac/Vdc free voltage versions
- Distance trimmer clutch for mechanical background suppression models

APPLICATIONS

- Automatic machines
- Transportation lines
- Wood working machines
- Automatic warehouses

SPECIFICATIONS

Approvals	CE, UL
Dimension (mm)	25 x 100 x 70
Distance Max	50000 mm
Distance Min	0 mm

Electrical connection	Terminal
IP Class	IP67
LED indicator	Yes
Lens material	PC
Light type	IR LED
Material of body	PBT
Output	NC, NO, Relay
Output current max	3 A
Photocell technology	Through beam emitter
Reaction time	25 ms
Sensitivity setting	No
Supply voltage	24-240 V AC/24-60 V DC
Temperature range bearing, from	-25 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	55 °C
Timer	No
Type of light	LED
Weight	130 g



