

SURFACE MOUNTED LUMINAIRE L/LO

12080106

L195 surface luminaire, turnable, D-ESGd-0-3M-55

- Linear design, surface mounted, length 195 - 720mm.
- Anodised aluminium housing, IP67
- 3m connecting cable or M12 connector
- Diffuse acrylic, diffuse or clear safety glass cover (LO with 30° or 60° lens)
- Color temperature 4000 or 5700K



PRODUCT DESCRIPTION

LED surface mounted luminaire L is a true master of transformation. In the linear version, it is available in four different lengths and two installations types. Any lighting issues inside a machine can be solved by installing the LED surface mounted luminaire L with a swivel mount. With the static mount option, the installation height is 25 mm. The version with the swivel mount does require an installation height of around 37 mm, but it affords the benefit of unique positioning and illumination. The anodised aluminium housing has an IP67 protection rating, meaning it is resistant to splashing water and dust. The LED surface mounted luminaire L can withstand even the toughest of applications.

The LED surface mounted luminaire L comes with your choice of a 3 metre cable or M12 connector as standard. For the light cover, you can select from diffuse acrylic glass and diffuse single-pane safety glass. The diffuse acrylic glass light cover has been selected specifically for this luminaire in order to achieve uniform illumination without the disruptive phenomenon of multiple shadows.

SPECIFICATIONS

| | |
|------------------------|-----------|
| Colour temperature | 5700 K |
| Height | 36.5 mm |
| IP Class | IP67 |
| Length | 238 mm |
| Lumen | 603 lm |
| Material Case | Aluminium |
| Material Glass | ESG d |
| Power Consumption | 5.3 W |
| Supply voltage | 24 V DC |
| Temperature range from | -21 °C |
| Temperature range to | 45 °C |
| Width | 40 mm |