

SURFACE MOUNTED LUMINAIRE FL/FLS

15070230

FLS450 surface luminaire ESGk-0-M8-40



- Flat design, surface mounted, length 150 - 450mm
- Anodised aluminium housing, IP67
- 3m connecting cable or M8 connector
- Diffuse acrylic, diffuse or clear safety glass cover
- Color temperature 4000 or 5700K

PRODUCT DESCRIPTION

Available in four different lengths, our LED surface mounted luminaire FLS boasts an impressively small installation height of just 17,5 mm. Its anodised aluminium housing has an IP67 protection rating, with its flat design and resistance to splashing water and dust ensuring it can withstand any challenges, even close up.

The LED surface mounted luminaire FLS comes with your choice of a 3 metre cable or M8 connector as standard. For the light cover, you can select from diffuse acrylic glass and diffuse single-pane safety glass. There is even a version with clear single-pane safety glass for applications requiring more light.

SPECIFICATIONS

| | |
|------------------------|---------|
| Colour rendering index | ≥80 |
| Colour temperature | 4000 K |
| Height | 17.5 mm |
| IP Class | IP67 |
| Length | 450 mm |
| Lumen | 3216 lm |
| Material Glass | ESG c |
| Power Consumption | 28 W |
| Supply voltage | 24 V DC |
| Temperature range from | -20 °C |
| Temperature range to | 45 °C |
| Width | 70 mm |