RECESSED LUMINAIRE T

15070254
T250 recessed luminaire DIFF-0-M12-55



- Flat design, recessed, length 250 or 450mm.
- Anodised aluminium housing, IP67
- 3m connecting cable or M8/M12 connector
- Diffuse acrylic, diffuse or clear safety glass cover
- Color temperature 4000 or 5700K

PRODUCT DESCRIPTION

The design of the LED recessed luminaire T is extremely flat. As a recessed machine luminaire, its installation height is just 3 mm when built in and it is available in two different lengths. It goes without saying that the recessed version of the anodised aluminium housing also has an IP67 protection rating and is resistant to splashing water and dust.

The LED recessed luminaire T comes with your choice of a 3 metre cable, M8 connector or M12 connector as standard. For the light cover, you can select from diffuse acrylic glass and diffuse single-pane safety
glass. If your application requires more light, there is even a version of this luminaire with clear single-pane safety glass.

SPECIFICATIONS

Colour rendering index	≥80
Colour temperature	5700 K
Height	20 mm
IP Class	IP67
Length	244 mm
Lumen	1608 lm
Material Case	Aluminium
Material Glass	PMMA
Power Consumption	14 W
Supply voltage	24 V DC
Temperature range from	-20 °C
Temperature range to	45 °C
Width	94 mm