

SURFACE MOUNTED LUMINAIRE LR40

15070600

LR40 365 surface luminaire, 30° lens, D-ESGd-30-M12-55

- Surface mount linear light, length 190 - 1070mm.
- Anodised aluminium housing, IP67
- M12 connector
- Color temperature 4000 or 5700K
- Models equipped with 30° or 60° lens available



PRODUCT DESCRIPTION

Its variety of features and configuration options, such as different light temperatures, cover types, optics and length variants make the LR40 a genuine all-rounder among industrial luminaires. Naturally, eco mode is an integral part of our new model. The position of the rotatable fastening elements allows an easy change of often used machine lights with a 40mm circular shape, without any design change in the machine. Up to four of LR40 715 can be cascaded. Machines can therefore be illuminated over a larger space with just one power source.

Optionally the LR40 can be complemented with a focussing lens which is available with 30 or 60 degrees optics. The use of diffuse safety glass enables the homogeneous light distribution despite the focus of the light.

SPECIFICATIONS

| | |
|-------------------------------|---------|
| Colour temperature | 5700 K |
| Height | 42 mm |
| IP Class | IP67 |
| Length | 365 mm |
| Material Glass | ESG d |
| Power Consumption | 10.39 W |
| Supply voltage | 24 V DC |
| Temperature range from | -20 °C |
| Temperature range to | 45 °C |