

## SURFACE MOUNTED LUMINAIRE LR70

15070633

LR70 510 surface luminaire, static, D-ESGd-O-M12-55

- Surface mount linear light, length 190 - 1070mm.
- Anodised aluminium housing, IP67
- M12 connector
- Color temperature 4000 or 5700K
- Models equipped with 30° or 60° lens available



### PRODUCT DESCRIPTION

Its variety of features and configuration options, such as different light temperatures, cover types, optics and length variants make the LR70 a genuine all-rounder among industrial luminaires. Naturally, eco mode is an integral part of our new model. The position of the rotatable fastening elements allows an easy change of often used machine lights with a 70mm circular shape, without any design change in the machine. Also for retrofit at machines with conventional light this series is suitable. Up to three of LR70 1070 can be cascaded. Machines can therefore be illuminated over a larger space with just one power source.

Optionally the LR70 can be complemented with a focussing lens which is available with 30 or 60 degrees optics. The use of diffuse safety glass enables the homogeneous light distribution despite the focus of the light.

### SPECIFICATIONS

<b>Colour temperature</b>	5700 K
<b>IP Class</b>	IP67
<b>Length</b>	510 mm
<b>Material Glass</b>	ESG d
<b>Power Consumption</b>	13.6 W