

## POWER SUPPLY 1-PHASE WITH BUILT IN REDUNDANCY, 24 V DC DIMENSION C SERIES, GENERATION 2

CP10.241-R1 Redundant PSU 100-240 V AC/24 V DC, 10 A

- Output current of 10 or 20 A
- Efficiency up to 95.2%
- 20% power reserves
- Built-in decoupling mosfet for 1+1 and n+1 redundancy
- Hot-Swap



**PULS** 

## PRODUCT DESCRIPTION

Click below link to download the white paper Efficient redundancy for power supplies

Also visit our page for Redundancy Modules

The Dimension CP-Series are cost optimized power supplies without compromising quality, reliability and performance. The most outstanding features of the CP20.241–R1/-R2/-R3 units are the high efficiency, electronic inrush current limitation, active PFC, wide operational temperature range and the extraordinary small size. The units include a decoupling MOSFET for building 1+1 or n+1 redundant power supply systems.

These redundancy power supplies come with three connection terminal options; screw terminals, spring-clamp terminals or plug connector terminals which allows replacement on an active application.

CP20.242-R2 version feature an enhanced DC input voltage range and the CP20.241-R2-C1 is additionally equipped with conformal coated pc-boards. CP10.242-R2 version feature an enhanced DC input voltage range.

With high immunity to transients and power surges, low electromagnetic emission, a DC-OK signal contact for remote monitoring, and a large international approval package, makes this unit suitable for nearly every application.


- AC 100-240V Wide-range Input
- Width only 39 or 48 mm
- Built-in Decoupling Mosfet for 1+1 and n+1 Redundancy
- Efficiency up to 94.7%
- 20% Output Power Reserves
- Safe HiccupPLUS Overload Mode
- Easy Fuse Breaking 3 times nominal current for 12ms
- Active Power Factor Correction (PFC)
- Minimal Inrush Current Surge
- DC-OK Relay Contact
- Current Sharing Feature Included
- 3 Year Warranty


## **SPECIFICATIONS**


Input voltage range	Wide-range
Number of phases	1
Input voltage AC	100-240 V


Input voltage ac min	85 V AC
Input voltage ac max	264 V AC
Input voltage DC	110-150 V
Input voltage dc min	88 V DC
Input voltage dc max	180 V DC
Inrush current at 120 V ac typical	6 A
Input current at 230 V ac typical	9 A
Power Factor at 120 V AC, full load. Typical	0.99
Power Factor at 230 V AC, full load. Typical	0.97
Supply Frequency	50-60 ±6 %
Power Consumption At 120 V AC	2.17 A
Power Consumption At 230 V AC	1.14 A
Outouturalteres	041/400
Output voltage	24 V DC
Output voltage min	24 V DC
Output Voltage max	28 V DC
Output Current  Effect	10 A
Power Reduction Of 60 To 70 ° C	240 W
	6 W/°C
Ripple. max	50 mV pp
Temperature Range Without Derating From	-25 °C
Temperature Range Without Derating To	60 °C
Efficiency At 120 V AC, full load. Typical	93 %
Efficiency At 230 V AC. Typical	93.9 %
Efficiency At 230 V AC, full load. Typical	94.7 %
Lifetime at 120 V ac, full load and +40 ° C	78000 h
Lifetime at 230 V ac, full load and +40 ° C	109000 h
MTBF (IEC 61709) 230 V AC, Maximum Load, 40 $^{\circ}$ C	641000 h
Width	39 mm
Height	124 mm
Depth	117 mm
Weight	0.6 kg

Clamp type	Spring-clamp
Series	Dimension C
Approvals	ATEX, CE, CSA US, cULus, IECEx
DC relay output	Yes
Material Protection	Aluminium
Hold-up time at 120 V AC, full load. Typical.	37 ms
Hold-up time at 230 V AC, full load. Typical.	37 ms
IP Class	IP20
Active Transient	Yes









	0.75mm <sup>2</sup>	1.0mm <sup>2</sup>	1.5mm²	2.5mm <sup>2</sup>
C-2A	30 m	37 m	54 m	84 m
C-3A	25 m	30 m	46 m	69 m
C-4A	9 m	15 m	25 m	34 m
C-6A	3 m	3 m	4 m	7 m
C-8A		2.		
B-6A	12 m	15 m	21 m	34 m
B-10A	3 m	3 m	4 m	9 m
D.12A	2 m	2 m	3 m	6 m

Don't forget to consider twice the distance to the load (or cable length) nen calculating the total wire length (+ and – wire).



