

NON ILLUMINATED SELECTOR SWITCH

Short Lever Handle

L21KA01

Selector Handle 2 Position Stable 45° Red

- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Optional lever colours



PRODUCT DESCRIPTION

Non illuminated selector switch head with a short lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K. Combine with separate clip and contact blocks to make complete switch assembly.

Standard body colour is grey with a black lever but also available with red, green & grey lever please enquire for more details.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

SPECIFICATIONS

Angle	45°
Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Stable
Illuminated	No
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Number of positions	2
Protection Class	II (double insulated)

Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Short lever
Weight	17,8 g

