

## NON ILLUMINATED MUSHROOM

### Mushroom Head

L21AC01  
MUSH-HD DIA32 SP-RTN RED

- IP66 / IP69K
- Non latching spring return
- Diameter 32mm, 40mm & 70mm heads



### PRODUCT DESCRIPTION

Spring return (non latching) mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where repetitive activation is required to help avoid stress or fatigue to the operator. The 40mm heads are well matched to the base of a closed fist and the 70mm heads the flat palm of a hand.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

### SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Protection Class	II (double insulated)
Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C

Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Mushroom ø32mm
Weight	18,8 g

