

ILLUMINATED MUSHROOM

Mushroom Head

L21AL10
MUSH-HD DIA32 SP-RTN ILL RED

- IP66 / IP69K
- Non latching spring return
- Diameter 32mm head
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Illuminated spring return (non latching) mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K
Ideal for applications where repetitive activation is required to help avoid stress or fatigue to the operator.

Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C

