BACO®

LEGEND PLATES

Legend plate frames & inserts

LIA9-382

- Standard or large width frames
- 5 legend insert colour options
- Option for custom engraved texts
- Option for twin touch head

PRODUCT DESCRIPTION

Legend plate frames are mounted on the pushbutton head before installation in the panel and the inserts are simply snaped into the legend plate frame.
Inserts are available in red, black, white, transparent or standard silver.
LIAx are standard width inserts for 2 lines of up to 13 characters.
LIBx are large width inserts for 2 lines of up to 18 characters.
LWP3 is the standard frame for LIAx inserts.
LWG3 is the standard frame for LIBx inserts.
LWP4 is a square profile frame for LIAx inserts
LWP2 is for twin & tripple touch heads for LIAx inserts.

All options below are for blank legend plate inserts but we can offer a wide range of pre engraved inserts of standard texts or symbols. We can also custom engrave the inserts to your exact requirement, please contact us for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Grey
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C

Standardtext

Text	Kod	Text	Kod	Text	Kod	Text	Kod	
Alarm	521	Hand - 0 - Auto	591	Power On	330	Start	301	
Auto	513	Hand - Auto	583	Raise	307	Stop	302	
Close	314	Jog	328	Reset	315	Tripped	3327	
Down	336	Lower	308	Reverse	306	Up	335	
Fast	310	Off	304	Run	327	0 - I	081	
Forward	305	On	303	Running	3326	0 - I - Start	093	
Hand	524	Open	313	Slow	309	I - 0 - II	091	

Standardsymboler ISO/DIN

Beskrivning	Symbol	Kod	Beskrivning	Symbol	Kod	Beskrivning	Symbol	Kod
Rак fortlöpande rörelse ISO 1		A01	Frigörა, lossa ISO 64A		A64	Gripa ISO 72/ DIN 46		A74
Alternerande rак rörelse ISO 5		A05	Frigöra, lossa ISO 64D		B64	Släppa ISO 73/ DIN 46		A75
Roterande fortlöpande rörelse medsols ISO 15/DIN 100		A07	Bromsa ISO 65		A65	Varning, pågående kraft ISO 8/DIN 45		A82
Roterande fortlöpande rörelse motsols ISO 76		B07	Frigöra broms ISO 66		A66	Huvudbrytare ISO 94		A94
Framåt ISO 16	Wh	A16	Automatiskt cykel eller semiautomatiskt ISO 67		A67	Smörjsmörjedyse ISO 121		C21
Vänsterläning ISO 35	+	A29	Manuell kontroll ISO 68		A68	Belysning ISO 122/ DIN 136		C03
Vänstervägning ISO 35		A29	«ON» Sluta strömmets ISO 69		A69	Rundsmörjning ISO 107/DIN 173		C07
Justerbar ISO 60		A62	«STOP» Öppna strömmets ISO 70		A70	Blås ISO 108/ DIN 264		C09
Klämma fixip, press ISO 63A		A63	ON/OFF slutа + öppna strömmets ISO 71		A71	Sug ISO 109/ DIN 264		C06
Klämma fixip, press ISO 63B		B63	Sluta strömmets, manuell impuls ISO 72/ DIN 166		A70	(Ljud) Alarm DIN 100		D01

Tillägg standardsymboler

B01	E01	F01	B92	B92	P62	D03	D04	D05
	I					II	III	IV