EMERGENCY STOP STATION

Key reset

LBX11201
EMERGENCY STOP ENCLOSURE GERMAN TEXT
KEY



- Conforms to ISO13850
- Contact blocks fixed behind lid
- 1 or 2 N/C contacts
- IP66

PRODUCT DESCRIPTION

Emergency stop control station that conforms to ISO13850 with a Ø40mm key to rest mushroom head.
The mushroom head has a yellow ring that is only visible in the deactivated position giving a clear visual indication when activated.
The enclosures can be supplied with texts and symbols please contact us for more information.
The contact blocks are not rear mounted in the station. They are fixed to the head with a standard clip so that the contacts remain attached to the head if the cover is removed.
New emergency stop marking according to ISO 13850
Our emergency shutdown products according to ISO13850 will be re-labelled to conform to the updated Emergency Stop Standard: DIN EN ISO 13850: 2016-05 (E) Machine Safety - Emergency Stop Function - Standard for Design (ISO 13850: 12/2015).
Products affected by the change are:
Emergency stop with "trigger-action function"
Emergency stop caps
Emergency stop signs
The change does not affect the suitability, functionality and reliability of the products.
The main features of the changes: text and symbol from IEC 60417-5638 according to
ISO 13850: 2015 Standard Requirements.

SPECIFICATIONS

Contact type	1 NC
Function	Key turn to reset
Color	Red
Color enclosure	Yellow, Black
Text language	German

IP Class	IP66
Impact resistance	IK05, IK07

Protection Class	II (double insulated)
Cable entry	2xM16/M20
Temperature range from	-25 °C
Temperature range to	70 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Approvals	BV, CB, CE, CSA 22.2, UL 508
Climate-resistant heat	IEC 60068-2-30
Climate resistance to sea air	IEC 60068-2-52
Climate resistance cyclic damp heat	IEC 60068-2-3
Flag indicator	No





