

CONTROL BOXES, COMPLETE

LBX324530



PRODUCT DESCRIPTION

Enclosures fitted with different functions.

The coated enclosures we present here are a few standard models, and a very small part of what is available. When it comes to coated enclosures and its features, they differ greatly from application to application. We have therefore specialized in customizing enclosures in the Baco range. Everything from smaller to large series.

We customize everything from the various combinations of pushbuttons, knobs, emergency stops, etc., to also arrange special texts or symbols on the enclosure or buttons.

Contact us for more information on this and we will help you to get a good solution.

Of course, it is also easy to order loose parts and assemble them yourself.

SPECIFICATIONS

Approvals	BV, CB, CE, CSA 22.2, UL 508
Cable entry	2xM16/M20
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Blue, Green, Red
Color enclosure	Grey, Yellow, Black
Contact type	2 NO, 2 NC
Impact resistance	IK05, IK07
IP Class	IP66

Protection Class	II
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C

