

NON ILLUMINATED MUSHROOM

Mushroom Head

L21AC01 MUSH-HD DIA32 SP-RTN RED

- IP66 / IP69K
- Non latching spring return
- Diameter 32mm, 40mm & 70mm heads





PRODUCT DESCRIPTION

Spring return (non latching) mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where repetitive activation is required to help avoid stress or fatigue to the operator. The 40mm heads are well matched to the base of a closed fist and the 70mm heads the flat palm of a hand.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Protection Class	II (double insulated)
Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C

Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Mushroom ø32mm
Weight	18.8 g

