

## NON ILLUMINATED MUSHROOM

### Mushroom Head

L21AC01  
MUSH-HD DIA32 SP-RTN RED

- IP66 / IP69K
- Non latching spring return
- Diameter 32mm, 40mm & 70mm heads



### PRODUCT DESCRIPTION

Spring return (non latching) mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where repetitive activation is required to help avoid stress or fatigue to the operator. The 40mm heads are well matched to the base of a closed fist and the 70mm heads the flat palm of a hand.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

## SPECIFICATIONS

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Red
<b>Function</b>	Spring return
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05
<b>IP Class</b>	IP66, IP69, IP69K
<b>Protection Class</b>	II (double insulated)
<b>Recommended Torque</b>	3
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	70 °C
<b>Temperature range from</b>	-25 °C

Temperature range to	70 °C
Type/Model	Mushroom ø32mm
Weight	18.8 g

