

NON ILLUMINATED PUSHBUTTON

Non Flush Head

L21CB02

PUSH-B NON-FL LATCH GREEN

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol



PRODUCT DESCRIPTION

Non flush (projecting) pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where an easier activation is required for example when wearing gloves.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Available in multiple colours in spring return or latching.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

| | |
|-------------------------------------|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Green |
| Function | Push Push |
| Illuminated | No |
| Impact resistance | IK05 |
| IP Class | IP66, IP69, IP69K |
| Protection Class | II (double insulated) |
| Recommended Torque | 3 |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 70 °C |

| | |
|------------------------|----------------------|
| Temperature range from | -25 °C |
| Temperature range to | 70 °C |
| Type/Model | Non flush pushbutton |
| Weight | 15.8 g |

