ILLUMINATED PUSHBUTTON

Flush Head

L21AH10
PUSH-B FLUSH SP-RTN ILL RED



- IP66 / IP69K
- Spring return or latching
- Optional text or symbol
- Illuminate with LED blocks

PRODUCT DESCRIPTION

Standard illuminated flush pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.
Available in multiple colours in spring return or latching.
Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.
Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Color Lens	Red
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Protection Class	II (double insulated)
Protection rating front of panel	IP69K
Recommended Torque	3
Temperature range bearing, from	-40 °C

Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Flush pushbutton
Weight	15.8 g

