

ILLUMINATED PUSHBUTTON

Non Flush Head

L21CK20
 PUSH-B NON-FL LATCH ILL GREEN

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Non flush (projecting) illuminated pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where an easier activation is required for example when wearing gloves.

Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.

Available in multiple colours in spring return or latching.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Green
Function	Push Push
Illuminated	Yes
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Protection Class	II (double insulated)
Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C

Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Non flush pushbutton
Weight	15.8 g

