

TWIN TOUCH NON FLUSH

Non Illuminated

L61QB21B

TWNPUSH GRN-RED (PROJ)

- IP66
- Flush & projecting buttons
- Spring return
- Various colours & symbols



PRODUCT DESCRIPTION

Non illuminated flush & projecting twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip and contact blocks to make complete twin touch assembly.

Available in various colour / text / symbol combinations.

All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Green/red
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP Class	IP66

Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Twin touch non-flush

