

## TRIPLE TOUCH

Non Illuminated

L61BA22  
TRIPLE TOUCH ARROW UP/DOWN/STOP

- IP66
- Flush pushbuttons
- Spring return
- Centre projecting button



### PRODUCT DESCRIPTION

Non illuminated triple touch heads that mount in a 22.5mm hole with protection rating IP66  
The buttons top and bottom are flush with a projecting centre button.

Combine with separate 333E clip and contact blocks to make complete triple touch assembly.  
Available in various colour / text / symbol combinations.  
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.  
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

### SPECIFICATIONS

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Green/red/green
<b>Function</b>	Spring return
<b>Illuminated</b>	No
<b>Impact resistance</b>	IK05
<b>IP Class</b>	IP66

Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Triple touch

