TWIN TOUCH NON FLUSH

Illuminated

L61QK21
TWINPUSH 1-0 GRN-RED PROJ IND



- IP66
- Flush & projecting buttons
- Spring return
- Illuminate with LED blocks

PRODUCT DESCRIPTION

Illuminated flush & projecting twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip, contact blocks & LED module (must be in centre position) to make complete twin touch assembly. The central part of the head is translucent and illuminate according to the colour of LED block used.

Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

SPECIFICATIONS

Type/Model	Twin touch non-flush
Function	Spring return
Color	Green/red
Color Lens	Clear
Illuminated	Yes

IP Class	IP66
Impact resistance	IK05
Temperature range from	-25 °C

Temperature range to	70 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Approvals	UL 508, CSA 22.2, BV, CB, CE
Recommended Torque	3
Climate-resistant heat	IEC 60068-2-30
Climate resistance to sea air	IEC 60068-2-52
Climate resistance cyclic damp heat	IEC 60068-2-3

