

ILLUMINATED SELECTOR SWITCH

Long Lever Handle

L21KV30
SEL-SWITCH ILL 2 POS LONG BLK

- IP66 / IP69K
- 2 or 3 position
- Illuminate with LED blocks
- Black lever with translucent surround



PRODUCT DESCRIPTION

Illuminated selector switch head with a long lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated selector switch assembly.

The central part of the switch head, side and tip of the lever are translucent and illuminate according to the colour of LED block used.
The lever of the switch is solid in colour and available only in black.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

SPECIFICATIONS

Angle	45°
Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Black
Function	Stable
Illuminated	Yes
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Number of positions	2

Protection Class	II (double insulated)
Recommended Torque	3
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Long lever
Weight	17.8 g

