

CONTACT BLOCKS

Faston flat blade terminals

33D01

CONTACT BLOCK NC FASTON

- Accepts spade crimp terminals
- Faston 6.35mm or 2 x 2.8mm
- Use with 1, 3 or 5 position clips



PRODUCT DESCRIPTION

Contact blocks with Faston flat blade terminals offer a fast and secure connection method.

Use with Faston 6.35mm or 2 x 2.8mm spade crimp terminals.

Snap directly onto 1, 3 or 5 position clips.

A second row can be stacked directly up to 3 wide to achieve a maximum of 6 contacts.

Available in N/O or N/C blocks.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Connection	Faston
Contact type	1 NC
Conventional free air thermal current Ith (AC15)	10 A
Conventional free air thermal current Ith (DC13)	2.5 A
Faston Size	6.35mm / 2 x 2.8mm
Lifespan Electrical	1 million cycles @ AC15: 120 V 3 A, 240 V 1,5 A. DC13: 125 V 0,22 A, 250 V 0,1 A.
Minimum operating current Ie (24Vdc)	5 mA

Protection rating rear of panel	IP20
Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	6 kV
Rated insulation voltage ac (IEC 60947-1)	320 V
Rated insulation voltage ac (UL 508)	300 V
Rated operating current Ie (AC15/120V)	6 A
Rated operating current Ie (AC15/240V)	3 A
Rated operating current Ie (DC13/125V)	0.55 A
Rated operating current Ie (DC13/250V)	0.27 A
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Weight	17 g

