

LED BLOCKS

Push in screwless terminals

33RAYL
LED BLOCK SP-CLAMP 24V YELLOW

- Quick connection with no tools required
- Long lifetime up to 100,000 hours
- 5 colour & 3 voltage options
- Finger safe IP20 terminals



PRODUCT DESCRIPTION

LED blocks with push in screwless terminals offer a fast and secure connection method. Snap directly in the centre position of 1, 3 or 5 position clips. Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads. Available in colour options, red, green, yellow, white & blue. Available in voltage options 12-24Vac/dc, 130Vac & 230Vac. Long lifetime of up to 100,000 hours.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Yellow
Connection solid wire max	2.5 mm ²
Connection stranded wire with ferrule max	1.5 mm ²
Connection stranded wire with ferrule min	0.5 mm ²
Frequenze	50/60 Hz
LED supply voltage	12-24V AC/DC
LED Voltage Tolerance	± 20%

Lifetime at rated supply voltage (25°C)	100000 h
Power consumption	25 mA ±20%
Protection rating rear of panel	IP20
Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Rated insulation voltage Ui	300 V
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Weight	19 g

