

LED BLOCKS

Faston flat blade terminals

33DAYH

LED 230V AC YELLOW, FASTON

- Accepts spade crimp terminals
- Faston 6.35mm or 2 x 2.8mm
- Long lifetime up to 100,000 hours
- 5 colour & 3 voltage options



PRODUCT DESCRIPTION

LED blocks with Faston flat blade terminals offer a fast and secure connection method. Use with Faston 6.35mm or 2 x 2.8mm spade crimp terminals. Snap directly in the centre position of 1, 3 or 5 position clips. Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads. Available in colour options, red, green, yellow, white & blue. Available in voltage options 12-24Vac/dc, 130Vac & 230Vac. Long lifetime of up to 100,000 hours.

SPECIFICATIONS

| | |
|---|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Yellow |
| Faston Size | 6.35mm / 2 x 2.8mm |
| Frequenze | 50/60 Hz |
| LED supply voltage | 230V AC |
| LED Voltage Tolerance | ± 30% |
| Lifetime at rated supply voltage (25°C) | 100000 h |

| | |
|---|-----------------|
| Power consumption | 16 mA \pm 30% |
| Protection rating rear of panel | IP20 |
| Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3) | 4 kV |
| Rated insulation voltage Ui | 300 V |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 70 °C |
| Temperature range from | -25 °C |
| Temperature range to | 70 °C |
| Weight | 17 g |

