

**PUSHBUTTON ENCLOSURES**

LBX0100  
BOX EMPTY 1 HOLE GREY LID

- 1, 2, 3, 4 and 5 hole pushbutton enclosures
- Pushbutton enclosure contact blocks



**PRODUCT DESCRIPTION**

	1 hole	2 holes	3 holes	4 holes	5 holes
Grey Lid					
<b>Order no.</b>	LBX0100	LBX0200	LBX0300	LBX0400	LBX0500
Yellow Lid					
<b>Order no.</b>	LBX0100J				

**PUSHBUTTON ENCLOSURE CONTACTS**

<b>Order no.</b>	
33S01	
33S10	

	Red	Green	Yellow	White	Blue
24 V AC/DC LED					
<b>Order no.</b>	33SARL	33SAGL	33SAYL	33SAWL	33SABL

130 V AC LED					
<b>Order no.</b>	33SARM	33SAGM	33SAYM	33SAWM	33SABM
230 V AC LED					
<b>Order no.</b>	33SARH	33SAGH	33SAYH	33SAWH	33SABH

## SPECIFICATIONS

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Cable entry</b>	2xM16/M20
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color enclosure</b>	Grey, Black
<b>Impact resistance</b>	IK07
<b>IP Class</b>	IP66
<b>Protection Class</b>	II
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	70 °C
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	70 °C

