

## CONTROL BOXES, COMPLETE

LBX10110  
BOX GREEN PUSH-B "START"



### PRODUCT DESCRIPTION

Enclosures fitted with different functions.

The coated enclosures we present here are a few standard models, and a very small part of what is available. When it comes to coated enclosures and its features, they differ greatly from application to application. We have therefore specialized in customizing enclosures in the Baco range. Everything from smaller to large series.

We customize everything from the various combinations of pushbuttons, knobs, emergency stops, etc., to also arrange special texts or symbols on the enclosure or buttons.

Contact us for more information on this and we will help you to get a good solution.

Of course, it is also easy to order loose parts and assemble them yourself.

## SPECIFICATIONS

<b>Approvals</b>	UL 508, CSA 22.2, BV, CB, CE
<b>Cable entry</b>	2xM16/M20
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Green
<b>Color enclosure</b>	Grey, Black
<b>Contact type</b>	1NO
<b>Impact resistance</b>	IK05, IK07
<b>IP Class</b>	IP66

Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C

● Green

NO

13 14

①

