

## AUDIBLE WARNING BUZZERS

L22VA03L

Baco Buzzer 80dB 18-30V ac/dc

- Buzzer pulse or continuous sound
- IP66 / IP69K
- 80dB at a distance of 10cm
- 30,000h service life



### PRODUCT DESCRIPTION

## SPECIFICATIONS

<b>Approvals</b>	CE, CSA 22.2, IEC 60068-2-3, IEC 60068-2-30, IEC 60068-2-52, IEC 60068-2-6, IEC 60529, IEC 60947-1, IEC 60947-5-1, IEC 62262, UL, UL 508
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Climate resistance to sea air</b>	IEC 60068-2-52
<b>Climate-resistant heat</b>	IEC 60068-2-30
<b>Color</b>	Black
<b>Frequenze</b>	50/60 Hz
<b>Height</b>	29.7 mm
<b>Insulation voltage</b>	4 kV
<b>IP Class</b>	IP20, IP66, IP69, IP69K, NEMA Type 1, NEMA Type 2, NEMA Type 3, NEMA Type 3R, NEMA Type 3S, NEMA Type 4, NEMA Type 4X, NEMA Type 12
<b>Length</b>	48.8 mm
<b>Lifespan Electrical</b>	30.000 h
<b>Power Supply ACDC max</b>	30 V
<b>Power Supply ACDC min</b>	18 V
<b>Protection Class</b>	II
<b>Recommended Torque</b>	3
<b>Sound level</b>	80 dB
<b>Structural Depth</b>	37.2 mm
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	85 °C

Temperature range from	-25 °C
Temperature range to	70 °C
Weight	0.02 g

