

AUDIBLE WARNING BUZZERS

L22VA03H

Baco Buzzer 80dB 185-265V ac/dc

- Buzzer pulse or continuous sound
- IP66 / IP69K
- 80dB at a distance of 10cm
- 30,000h service life



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	CE, CSA 22.2, IEC 60068-2-3, IEC 60068-2-30, IEC 60068-2-52, IEC 60068-2-6, IEC 60529, IEC 60947-1, IEC 60947-5-1, IEC 62262, UL, UL 508
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Black
Frequenze	50/60 Hz
Height	29.7 mm
Insulation voltage	4 kV
IP Class	IP20, IP66, IP69, IP69K, NEMA Type 1, NEMA Type 2, NEMA Type 3, NEMA Type 3R, NEMA Type 3S, NEMA Type 4, NEMA Type 4X, NEMA Type 12
Length	48.8 mm
Lifespan Electrical	30.000 h
Power Supply ACDC max	265 V
Power Supply ACDC min	185 V
Protection Class	II
Recommended Torque	3
Sound level	80 dB
Structural Depth	37.2 mm
Temperature range bearing, from	-40 °C
Temperature range bearing, to	85 °C

Temperature range from -25 °C

Temperature range to 70 °C

Weight 0.02 g

