

## LEGEND PLATES

Legend plate frames & inserts

LIA9-093

- Standard or large width frames
- 5 legend insert colour options
- Option for custom engraved texts
- Option for twin touch head



## PRODUCT DESCRIPTION

Legend plate frames are mounted on the pushbutton head before installation in the panel and the inserts are simply snaped into the legend plate frame. Inserts are available in red, black, white, transparent or standard silver.

LIAx are standard width inserts for 2 lines of up to 13 characters.

LIBx are large width inserts for 2 lines of up to 18 characters.

LWP3 is the standard frame for LIAx inserts.

LWG3 is the standard frame for LIBx inserts.

LWP4 is a square profile frame for LIAx inserts

LWP2 is for twin & tripple touch heads for LIAx inserts.

All options below are for blank legend plate inserts but we can offer a wide range of pre engraved inserts of standard texts or symbols. We can also custom engrave the inserts to your exact requirement, please contact us for more details.

## SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Grey
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C

## BACO

Text	Kod	£	Text	Kod	Standardtext		Kod	Text	Kod		Text	Kod	Text			Standardtext Kod Text		Kod	Text	Kod	÷.
dave.	621	100	4.0. http:					Start	301	+	Alava	621	Hind . 0 . Acto			Phase On		380	5241	301	
uto .	613		and - Auto				307	500	322	-	Auto:	513 314 336 310	Hand - Auto		585	Rate		307	Stop	322	-
2008	314		Joo	328			315		3327		Cione				328			355	Troop	3327	-
Soan	316	-	Lower	308 Rivers 304 Run 303 Pump		14	308	Llo	335	-	Draws		-	Lower	308	Revorse		305	Ub	355	-
ant	310	_	01				307	0-1	061	+	Fast		+	01	304			307	0.1	061	-
Forward	305	-	On .			V0 333		6 O - J - Start	093	_	Forward	305	05		305	Burneg		325	0-J-Start	093	
Hand 524			Open 313		Slow		308	1-0-8	091	-	Hand	524	Open		313 Slow			309	1-0-8	091	-
				Stand	lardsymboler IS	O/DIN									Standards	symboler ISO/	DIN				
Seaming		Syntox	Kol	Bestmang		Bytheir	Kod	Beakhing	Syntax Kod		Seaming	Seaming		Red	Bestdoring		Bymbol	Ked	Beauting	Syntax	K KH
Has fortigands rivels IIIO 1			301	Papers, Loss 100 DAA				Dige 150 Nil Deviet		A34 -	Hain Yorkigaanda Hirekaa 180 1		0	40	Paging Lossa SID SAA		-	A64	Orga 150 Ité Ott-Ati		) ~
Alternarycle na cinata (3) Alfi		ADS	Pagina, Kena 100 Mil		0	204	Thippe 100 75/ (deute)	٢	- 4/9	Attorney de nativitation 1005	10.5 (md)		Project times 100 MC		0	284	04004 100.75/08L45	1	)		
All All		10	Bronal BO RE		0	ALC.	Survey phylocia leaf ISO 30000 45	4	AD			0	207	Brunau GO EL		0	All	Varieng plightnis kraft 150-32-081-45	4	) 10	
Adamanda torkiyaanda 160.75	una-toise mitais		-967	Pagos borns 100 Mil			Alt	Houdinteen 150 M	0	Alt	Roberston Gridgunde contra motalita 1902-78		0	867	Pagina bioma (80 M		0	All.	Hundinten 10094	0	) ^
Puesda 180 M			AM	Automatisk cylel (ske series.tonatisk) 150 57			AU	Bridghundspie 180 107		1001	Pundi 180.16			.836	Automatist (yiel (der samautomation) 60.07			AU	Bridghundycke 180 107		) =
Variantiring ISO 16		•	A28 Marcal special ISO 68		(D) MB		All	Between g		-001	Varianting 180.38		•	428	Marcal sprint GO M		٢	All	Belyaning ISO 1020 DAy 108	0	) ~
Notestania and a		$\Theta$	A29		-	0	Alb	Runsenbymg BD 107.0W 775	0	1007	Vikolanarakranji 1807.05		0	839	s-ON duta abdemana 00.08			Alb	Runandonig ISO 107.0W ITS	e	) •
Lenetar BD Gr		Ø m			(manala)	0	A10	1966 190 109/ 091254	())	1000	Admetar BD 62	v 🖉 A5		A82			0	A10	1966 100 109/ CIN 254	0	
Kilderen Pessi pressa 180 Kild		0	Att .	OVOIT site + core a 100 71	and the second s	0	An	Bug ISO 104 OW 254	3	COE	Karona Poju presa 180 Kon		0	Ad2	OuOFF suite - coping promisess (80.71		٢	Am	Bug BC TOX DN 264		) ~
Kärnen Pop press 100 620			m	Bully anonests, market 600 707 DRI 108	ad reputs	0	A72	East Name ON 105	(00)	001	Kierona Pogi presse 100 626			80	Buty promess, manual imp 60 72/104 108	ра	۲	A/2	SJuit Nami DALTIS	00	) 00
				Tillion	standardsymb	clar				-					TillAon star	ndardtymbole					-
		5 0	D		1	(N)	(11)					Č	5 0	1)			THE O	(11)			