

## TWIN TOUCH FLUSH

Non Illuminated

L61QA33F

Twintouch Flush Black Arrows Left Right

- IP66
- Flush pushbuttons
- Spring return
- Various colours & symbols



### PRODUCT DESCRIPTION

Non illuminated flush twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip and contact blocks to make complete twin touch assembly.

Available in various colour / text / symbol combinations.

All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

### SPECIFICATIONS

|  |                              |
|--|------------------------------|
| <b>Approvals</b>                           | BV, CB, CE, CSA 22.2, UL 508 |
| <b>Climate resistance cyclic damp heat</b> | IEC 60068-2-3                |
| <b>Climate resistance to sea air</b>       | IEC 60068-2-52               |
| <b>Climate-resistant heat</b>              | IEC 60068-2-30               |
| <b>Color</b>                               | Black/black                  |
| <b>Function</b>                            | Spring return                |
| <b>Illuminated</b>                         | No                           |
| <b>Impact resistance</b>                   | IK05                         |
| <b>IP Class</b>                            | IP66                         |
| <b>Recommended Torque</b>                  | 3                            |

|                                 |                  |
|---------------------------------|------------------|
| Temperature range bearing, from | -40 °C           |
| Temperature range bearing, to   | 70 °C            |
| Temperature range from          | -25 °C           |
| Temperature range to            | 70 °C            |
| Type/Model                      | Twin touch flush |

